



R. "LYNN" RUFFELL

316 West Milwaukee Street; P.O. Box 511
 New Hampton, IA 50659
 P: 800-222-6047 x230 IC: 208-569-4061
 lynn@zips.com | www.zips.com



- High Tensile Fabricated Construction with Tubular Crossmembers on 12" Centers for Optimum Support of Concentrated Loads
- DOT Approved Sealed Beam, Rubber Isolated LED Lighting; Wiring Routed Through Tubular Construction to Protect from the Environment
- Shot Blasted Followed by a Phosphate Wash and Seal provides Clean Base of Paint Adhesion. Epoxy Primer and an Enamel Top coat for a Durable Finish
- Hydraulics to transition ramp to an 12° load angle (standard off self contained power unit – also available to run off wet kit)
- Available in various configurations including
 - Fifthwheel or tag
 - Length and width
 - Tandem or triple axle
 - Various capacities available
- Various options available including
 - Wet kit in lieu of self contained power unit
 - D-rings or belt winches to specification
 - Outriggers
 - Hubometer
 - Custom paint & detail

TRAILMAX QUALITY, BACKED BY A 5-YEAR STRUCTURAL WARRANTY



Optional pull-out outriggers



Optional hydraulic jacks



Standard 20,000# winch




Standard tool boxes in fifthwheel area

"Setting the Industry Standard"

Maximum performance
 Maximum reliability
 Maximum return on investment

"For the Long Haul"



DECK WIDTH - 102"

Capacity (Distributed)	100,000 lbs.
Concentrated Load	70,000 lbs. in 10'
Base Trailer Weight	21,940 lbs.
Frame Construction	Fabricated Perimeter design A-656 high tensile
Crossmembers	8" Crossmembers on 12" centers
Hitch	Fifthwheel King Pin type
King Pin Setting	18"
Swing Clearance	82"
Loaded Deck Height	35"
Load Angle	12 degrees
Deck Width	102"
Landing Gear	2 Speed 70,000 lb., 100,000 lb. static load
Load Securement	2-way Chain Slot/Stake Pocket alternating 2' centers
Hydraulic System	Wet kit PTO hydraulic operation with controls at gooseneck
Tool Compartment	2 each 36" in 5th wheel area
Winch	12,000 lb Hydraulic with controls at gooseneck
Axles	3 each 23,000 lb. capacity
Hubs	Oil bath, Hub piloted with outboard drums, 8 hole bolt circle
Brakes	12-1/4" x 7-1/2" full air brakes with spring brakes all axles, automatic slack adjusters, equipped with 4S2M anti-lock braking system
Drums	Steel Outboard type
Suspension	Ridewell Model 240 Air Ride with dump valve
Wheels	17.5" x 6.75" Uni-mount 8 on 275mm bolt circle
Tires	235/75R 17.5 radial load range H
Finish	5 stage pre-treatment with two component epoxy primer and two component urethane enamel topcoat, standard color white
Electrical	Trucklite modular system with rubber isolated, sealed beam LED lighting
Decking	1 3/4" oak with fasteners at all cross members
Various Options	Spare Tire, Apitong Decking, Traction Devices, D-rings, Belt Winches, Outriggers, Custom Paint & Detail, Self Contained Power Unit

Specifications are subject to change without notice